

МОРОЗИЛЬНЫЕ КАМЕРЫ

ТЕХ. ХАРАКТЕРИСТИКИ

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-4159
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48

Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73

Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Саранск (8342)22-96-24
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35

Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35
Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

Адрес: <https://sagi.nt-rt.ru/> || эл.почта: sig@nt-rt.ru

NF51M



Blast chiller freezer multifunctional-5 trays-NOW

Multifunction, 5 GN1/1-EN60x40 containers. Temperature range -40°C - +85°C. Main functions: blast chilling, freezing, slow cooking, holding, proving and retarder-proving, defrosting, drying, pasteurisation, storage and many more. 7" touch display PCB and USB. Adjustable humidity. Probe with 3 sensors, with heating. Preset for connectivity to APOLINK portal.



Note	*Product Information (EN17032 – Commission Regulation EU 2015/1095)
------	---

General information

Supplier/producer 's name	SAGI
Series	NOW
Supplier's model identifier	NF51M
Category	blast chiller freezer multifunctional
Type	blast chiller-freezer
Line	catering - pastry&bakery - ice-cream

Technical features

Temperature range, °C	-40°/+85°C chamber
Yield from +90°C to +3°C (kg)	at product core, 25 – in 90 minutes
Yield from +90°C to -18°C (kg)	at product core, 15 – in 240 minutes
Yield from +65°C to +10°C (kg)	at product core, 25 – EN 22042 test
Yield from +65°C to -18°C (kg)	at product core, 15 – EN 22042 test
Energy consumption, kWh/kg	0,09 (chilling) - 0,28 (freezing)
Method for energy consumption	EN 22042
Climate class	5 (+40°C, 40% R.H.)
Refrigerant/GWP	R452A/2141
Refrigerant charge, kg	1
LWA dB(A)	65
Valves	thermostatic, compensation, liquid line solenoid
Condensation	air – integral cooling unit

NF51M



Defrosting	cycle reversal (hot gas)
Evaporation of condense drain	automatic with filament heating element
Fan system control	fan stops when door is opened (from 40% to 100%)
Humidity setting range	from 0% to 100% with humidity probe
Safety thermostat	cut-off 120°C
Water connection	3/4"
Refrigeration power -23,3°C W	1076 ashare conditions
Heating power, W	1000 – on front of battery for easier maintenance
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	1,6

Construction features

Structure	one-piece structure with rounded corners, with automatic heating of door contact perimeter
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	press-formed, with drain outlet
Structure profiles	High temperature Noryl
Insulation thickness, mm	60 - HFO foam
Worktop	30 mm thick – flame retardant and water repellent
Door	in AISI 304 stainless steel – door stop to keep it open and prevent odour formation
Joint de porte	with ten chambers, magnetic, easily replaceable
Standard hinging door	on the right / no-reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	frame in AISI 304 stainless steel
Positions (n.)/spaced, mm	5/65
Evaporator	triple circuit – cataphoresis anti-corrosion treatment and powder painting
Easymaintenance	tool-free access to condenser – steam injection counter for nebuliser maintenance
Safety interlock switch	yes, to stop internal fan
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	73 ÷ 103 (maximum appliance height 913 mm, minimum 878 mm)

Control and functions

Kinf of control	electronic circuit board mounted on door – USB – RS485 communication port
Software Update	with USB pen drive
Display	colour 7" touch screen
Connectivity	with APOLINK accessory for remote control – Industry 4.0
Alarms	optical and acoustical
Languages	IT – EN – ES – DE – FR – NL – DK – PT
Cold functions	Blast-chilling Soft/Hard; Blast-freezing Soft/Hard; Preservation; Precooling; Infinity

NF51M



Hot functions	Slow cooking; Thawing Heater; Hot keeping; Preheating; Drying; Pasteurization; Proofing
Automatic cycles	Blast-chilling; Blast-freezing; Slow cooking; Vacuum cooking; Proofing
Special cycles	I.F.R.; Anisakis; Yogurt; Chocolate cake; Pasteurization; Drying; Precooling; Preheating
Favourite programs	100: 30 blast-chilling; 30 blast-freezing; 20 slow cooking; 10 retarder prover; 10 thawing
HACCP	infinite events up to one year of recording
Alarms (no.)	saving of up to 40 events

Standard

Core probe	heated, 3 sensors, smart core sensor recognition-mounted on rear of door
Water collection bowl	stainless steel located under the appliance

Dimensions and weights

Packing (LxDxH), cm	81x84,5x107
Dimensions (LxDxH), cm	74,7x79,5x90
Net internal dimensions, cm	60x40x34 (LxDxH)
Gross Weight (kg)	130
Net Weight (kg)	120

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48

Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73

Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Саранск (8342)22-96-24
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35

Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35
Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

Адрес: <https://sagi.nt-rt.ru/> || эл.почта: sig@nt-rt.ru